



ContiTech

CERTIFICATE OF COMPLIANCE

Name and Location of Manufacture:

ContiTech Antriebssysteme GmbH
Continentalstr. 1
29451 Dannenberg
Germany
Fon : ++49 (0) 5861-806-324
Fax : ++49 (0) 5861-806-327

Date Issued: 21.03.2019

Contact:
andreas.pfannschmidt@ptg.contitech.de

Customer.

OTIS European Parts Center
106 avenue de la Pyramide
95 Roissy en France

France

The content of this certificate of compliance is in accordance with the order and the OTIS specification # D541_DRS_LCRCSB and meets or exceeds all referenced requirements.

OTIS Part Number : AAA717AJ1

OTIS specification : D541_DRS_LCRCSB (Rev.Date 2016-12-23),
DWG AAA717AJ

ContiTech designation : LCRCSB 34kN

Characteristics:

Construction :	Flat belt, containing 8 equal spaced steel cords, each has a diameter of 1,98 mm. Cords are 7x7 wires construction, encapsulated in polyurethane jacket.
Minimum wire tensile strength :	2750 N/mm ²
Dimensions of belt :	25,0 mm wide x 3,3 mm thick
Part of labeling:	EX AAA717AJ1 or M AAA717AJ1 or V AAA717AJ1
Belt weight / 100m :	18,6 kg (11,6 kg cords, 7 kg TPU)
Minimum breaking load of belt :	34kN

All standards referenced in this document are based on the latest revision levels.



CERTIFICATE OF COMPLIANCE



Harmonized Code Schedule

- I. **Product Description:** Coated Steel Belt
- II. **Specifications of Steel Wires:** Steel wire coated with polyurethane is the main component of the elevator belt.
- III. **Cord diameter:** The diameter of the cord is 1,98mm
- IV. **Type of steel:** Carbon steel
- V. **Type of coating:** Polyurethane coat
- VI. **Type of finish:** Carbon steel wires with a metallic zinc coating are referred to as galvanized wires.
- VII. **Identification key of the Product According to International Standards:**
Standard for the embedded cords:
 - ASTM D2969: cord diameter, breaking load, low load elongation, linear density

VIII. **Chemical composition percentage only of the chemical elements that make up the product:**
The carbon steel wires used in the elevator ropes have the following chemistry

Cord elements	%
C	0,70 – 0,75
S	< 0,03
Mn	< 0,55
P	< 0,03
Cu	< 0,1
Cr	< 0,1
Ni	< 0,1

The polyurethane coat is a thermoplastic Polyester-Polyurethane

IX. **Presentation of the Product:** Reel:



- X. **Integrated product accessories:** The belt is not integrated into other parts or assemblies.
- XI. **Dimensions of final product:** See page 1 for dimensions of belt



CERTIFICATE OF COMPLIANCE



We declare that the information contained in this certificate is true and correct.

Authorized Signature: <i>i. R. A. Pfannschmidt</i>		Company: ContiTech Antriebssysteme GmbH Continentalstr. 1 29451 Dannenberg Germany	
Name: Andreas Pfannschmidt		Title: Quality Manager	
Date: 21.03.2019	Telephone: ++49 (0) 5861-806-324	Fax: ++49 (0) 5861-806-327	E-Mail: andreas.pfannschmidt@ptg.contitech.de
This certificate is valid until 31.12.2019			

