

DATA SHEET DOOR DETECTOR 03.WELIG.J3.184

<p>SIL2 Certificate number: TÜV-A-AT-1/12/308CEES/1</p> <p>Certificate number: EN 62061 SIL2, PI d Standard / Norms: EN 13849 section 1 + section 2, ISO 22201, EN12016 Vibration resistance: EN60068 - 2 - 6 Shock resistance: EN60068-2-27 EMC rating = EN12016</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center;">Diodenpositionen</td> <td style="text-align: center;">J3</td> </tr> </table>	Diodenpositionen	J3																
Diodenpositionen	J3																		
<p>J3</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">Technical Specifications</th> </tr> </thead> <tbody> <tr> <td>Effective detecting distance (EDD)</td> <td>500 - 1500mm</td> </tr> <tr> <td>Active protection height (APH)</td> <td>50mm - 1837mm</td> </tr> <tr> <td>Working environment</td> <td>-20°C - 45°C, 100,000LUX. IP4X</td> </tr> <tr> <td>Tolerances</td> <td>Vert: 20mm±10°, Horiz: 3mm±7°</td> </tr> <tr> <td>Dimensions (HxWxD)</td> <td>2000mm x 43.2mm x 16.5mm</td> </tr> <tr> <td>Reaction time</td> <td>< 100ms</td> </tr> <tr> <td>Diodes / beams</td> <td>16 Diodes / 46 beams</td> </tr> <tr> <td>Signal output</td> <td>Relay output NO</td> </tr> </tbody> </table>	Technical Specifications		Effective detecting distance (EDD)	500 - 1500mm	Active protection height (APH)	50mm - 1837mm	Working environment	-20°C - 45°C, 100,000LUX. IP4X	Tolerances	Vert: 20mm±10°, Horiz: 3mm±7°	Dimensions (HxWxD)	2000mm x 43.2mm x 16.5mm	Reaction time	< 100ms	Diodes / beams	16 Diodes / 46 beams	Signal output	Relay output NO
Technical Specifications																			
Effective detecting distance (EDD)	500 - 1500mm																		
Active protection height (APH)	50mm - 1837mm																		
Working environment	-20°C - 45°C, 100,000LUX. IP4X																		
Tolerances	Vert: 20mm±10°, Horiz: 3mm±7°																		
Dimensions (HxWxD)	2000mm x 43.2mm x 16.5mm																		
Reaction time	< 100ms																		
Diodes / beams	16 Diodes / 46 beams																		
Signal output	Relay output NO																		